



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1051679	38	1-1/2	54	2,13	20	300	60	900	1,40	0,94	121	397
1383949	45	1-49/64	61	2,40	20	300	60	900	1,61	1,08	120	400
1210564	51	2	71	2,80	20	300	60	900	2,24	1,50	120	400
1211846	51	2	68	2,68	20	300	60	900	1,93	1,29	120	400



EN

Tank cleaning hose

Application: softwall hose used for cleaning tankers in the oil and chemical field with water and detergents.

Temperature: from -30°C (-22°F) to +100°C (+212°F).

Construction

Tube: black, smooth, SBR rubber resistant to detergents.

Reinforcement: high strength synthetic cord; stainless steel wires built into the body of the hose for the discharge of static electricity.

Cover: black, smooth (wrapped finish), SBR rubber, weathering and sea water resistant.

Also available upon request: 1. Different diameters 2. Hose cover supplied with yellow ring indicators to determine the working depth of the hose inside the tank.

CN

船仓清洗管

应用范围: 软壁软管，输送清洁剂或水用于清洗油轮和其它石油化学品储罐

温度范围: -30°C至+100°C

软管结构

内层: 黑色，光滑，耐清洁剂的SBR合成橡胶

加强层: 高强度合成线绳，内置防静电不锈钢丝

外层: 黑色，光滑(表面布纹)，耐海水侵蚀SBR合成橡胶

可选择项: 1. 不同口径; 2. 管子表面标有黄色环形标记，以确认进入工作区的长度

Above technical data are referring to applications at room temperature (+20°C).

IVG Colbachini is not liable for the use that differs from what is confirmed in their catalogues, product sheets, offers, order confirmations and contained recommendations. For a correct use refer to "Recommendations for the selection, storage, use and maintenance of rubber hoses" by Assogomma, available on www.ivgspa.it.

With the aim to improve the product, IVG reserves the right to modify the hose specifications without giving any prior notice.

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).