


code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1150685	76	3	94	3,70	6	90	18	270	2,84	1,91	60	200
1392050	90	3-35/64	103	4,06	6	90	18	270	2,30	1,55	60	200
1405926	102	4	112	4,41	5	75	15	225	1,94	1,30	60	200
1382624	102	4	120	4,73	5	75	15	225	3,82	2,57	60	200
1382829	102	4	122	4,81	6	90	18	270	4,31	2,90	60	200
1352555	110	4-21/64	123	4,85	6	90	18	270	2,80	1,88	60	200


**EN**

## Hose with white tube for delivery of dry abrasive materials

**Standards:** tube: Reg. EC 1935/04 and 2023/06. Phthalates free. FDA tit.21 art.177.2600 dry foods. BfR XXI Cat.4.

**Application:** softwall hose with anti abrasive white tube, suitable to convey with pneumatic systems abrasive foodstuff, dust, and PVC grains that must not be stained.

Not suitable for ATEX environments.

**Temperature:** from -30°C (-22°F) to +70°C (+158°F).

**Construction**

**Tube:** white, smooth NR/SBR rubber, resistant to abrasive dust and foodstuff.

**Reinforcement:** high strength synthetic plies and embedded copper wires.

**Cover:** black, smooth (wrapped finish), electrically conductive EPDM rubber.

**Branding:** red transfer "IVG TRUCK (family logo)..."

**Also available upon request:** 1. Different diameters. 2. Different working pressures. 3. Don bd with EPDM blue cover.

**RU**

## Рукав с белым внутренним слоем для подачи сухих абразивных материалов

**Нормативы:** внутренний слой соотв. CE 1935/04 и CE 2023/06. Без фталатов. FDA tit.21 сухие пищевые продукты. BfR Kat.4.

**Применение:** напорный рукав с белым антиабразивным внутренним слоем для подачи абразивных пищевых продуктов, порошков и гранул из ПВХ, которые не должны пачкаться. Не предназначен для употребления во взрывоопасной среде АТЕХ.

**Температура:** от -30° до +70°C.

**Конструкция**

**Внутренний слой:** белый, гладкий, из смеси натурального и синтетического каучука NR/SBR устойчивый к абразивным порошкам и продуктам.

**Усиление:** высокопрочный синтетический корд, встроенная стальная спираль.

**Покрытие:** чёрное, гладкое (с отпечатком текстильного бандажа) из токопроводящего каучука EPDM.

**Маркировка:** красная маркировочная лента "IVG Truck (логотип сферы применения)..."

**В наличии по запросу:** 1. Другие диаметры. 2. Другие давления. 3. DON bd с покрытием из состава EPDM синего цвета.



**Advice to users**  
on hoses in contact with food

**[www.ivgspa.it](http://www.ivgspa.it)**

## » Clean In Place information

- IVG recommends for the first use a wash cycle with potable water at a maximum temperature of 80°C/90°C and a hose sanitation as reported above before conveying food products.
- At the end of each cycle the equipment and hose assemblies must be cleaned and disinfected.
- Strictly follow the times indicated for each cleaning cycle.
- Do not immerse hose assembly in the sanitation fluid because only the inner tube is suitable for contact with the below mentioned solvents.
- Every cleaning cycle must be immediately followed by a complete rinse.
- Do not exceed 3 bar working pressure in CIP systems.

<b>HOSE*</b>	<b>Hot Water</b>	<b>Steam open end</b>	<b>H2O2 1%</b>	<b>H2O2 3%</b>	<b>Peracetic Acid 0.1%</b>
<b>FOOD SCOTLAND</b> <b>FOOD VINO FLEX</b> <b>FOOD TUSCANY</b> <b>FOOD PIEDMONT</b> <b>FOOD CANA</b> <b>TRUCK FOODFLEX®/IIR</b> <b>OFFSHORE PL POTABLE</b>	90°C 8 hours	Max 130°C 30 minutes	Max 70°C 15 minutes	Max 30°C 15 minutes	Max 50°C 15 minutes
<b>FOOD MILLENNIUM</b> <b>FOOD DAMASCO</b>	80°C 8 hours	Max 110°C 15 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes	Max 30°C 10 minutes
<b>TRUCK FOODFLEX®</b> <b>FOOD MERLOT</b> <b>FOOD PARRY</b>	80°C 8 hours	Max 110°C 15 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes	Max 30°C 10 minutes
<b>FOOD ALICANTE</b> <b>FOOD MILKSERVICE</b> <b>FOOD SUPERJUICE</b>	90°C 8 hours	Max 130°C 30 minutes	Max 70°C 15 minutes	Max 30°C 15 minutes	Max 50°C 15 minutes
<b>FOOD PANAMA</b> <b>FOOD ACAPULCO</b> <b>FOOD OILMILL</b>	80°C 8 hours	Max 110 °C 10 minutes	Max 50 °C 10 minutes	Max 30 °C 10 minutes	Max 30 °C 10 minutes
<b>FOOD ACQUABLU®</b>	80°C 8 hours	Max 110 °C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes	Max 70°C 30 minutes
<b>FOOD SHETLAND</b> <b>CHEM THUNDERFLEX</b> <b>CHEM SUPERTOP UPE</b>	90°C 12 hours	Max 130°C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes	Max 70°C 30 minutes
<b>TRUCK DON/BN</b> <b>TRUCK GORDON</b>	80°C 8 hours	Max 110°C 15 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes	Max 30°C 10 minutes

\* The indications regarding hoses on this list refer to the product code found in the IVG catalogue [www.ivgspa.it](http://www.ivgspa.it).

## » Clean In Place information

- Al primo utilizzo, IVG raccomanda di effettuare un ciclo di lavaggio con acqua potabile alla temperatura di 80°C/90°C e una sanificazione della manichetta prima di convogliare i prodotti alimentari.
- Al termine di ogni ciclo di utilizzo deve essere effettuata la detersione e la disinfezione delle manichette.
- Il rispetto dei tempi è fondamentale per ogni ciclo di lavaggio.
- Non immergere la manichetta nel liquido di sanificazione poiché solo il sottostrato è idoneo al contatto con i solventi indicati.
- Ogni ciclo di lavaggio deve essere immediatamente seguito da un risciacquo completo.
- Non utilizzare sistemi CIP oltre 3 bar di pressione.

Peracetic Acid 0.5%	Phosphoric Acid 5%	Chlorine 1%	NaOH 2%	NaOH 5%	Nitric Acid 0.1%	Nitric Acid 3%
Max 30°C 15 minutes	Max 80°C 15 minutes	Max 80°C 15 minutes	Max 80°C 15 minutes	Max 30°C 15 minutes	Max 70°C 15 minutes	Max 30°C 15 minutes
Max 30°C 10 minutes	Max 50°C 15 minutes	Max 70°C 15 minutes	Max 70°C 10 minutes	Max 30°C 10 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes
Max 30°C 10 minutes	Max 50°C 15 minutes	Max 70°C 15 minutes	Max 70°C 10 minutes	Max 30°C 10 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes
Max 30°C 15 minutes	Max 80°C 15 minutes	Max 80°C 15 minutes	Max 80°C 15 minutes	Max 30°C 15 minutes	Max 70°C 15 minutes	Max 30°C 15 minutes
Max 30 °C 10 minutes	Max 50 °C 10 minutes	Max 70 °C 10 minutes	Max 70 °C 10 minutes	Max 30 °C 10 minutes	Max 50 °C 10 minutes	Max 30 °C 10 minutes
Max 50°C 30 minutes	Max 80°C 30 minutes	Max 80°C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes
Max 50°C 30 minutes	Max 80°C 30 minutes	Max 80°C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes	Max 80°C 30 minutes	Max 50°C 30 minutes
Max 30°C 10 minutes	Max 50°C 15 minutes	Max 70°C 15 minutes	Max 70°C 15 minutes	Max 30°C 10 minutes	Max 50°C 10 minutes	Max 30°C 10 minutes

\* Le indicazioni riguardanti i tubi di questa lista fanno riferimento ai codici prodotto presenti nel catalogo IVG [www.ivgspa.it](http://www.ivgspa.it).



## General Advice

- Hoses are not meant to permanently contain the products they convey.
  - Store hoses away from direct sunlight and heat. When not in use store hoses with perforated plugs at both ends.
  - Before every use check the hose condition. The hose cover, especially in the fitting area, should show no signs of cuts, tears, or bubbles. There should be no hard or weak areas, signs of detachment or collapse.
  - Remember to guarantee traceability of every single piece of hose put into the market (CE 1935/2004, CE 2023/2006)
- 
- I tubi non sono idonei alla stagnazione permanente dei prodotti.
  - Stocca al riparo dalla luce e dal calore, con tappi forati alle estremità.
  - Verifica sempre le buone condizioni del tubo prima di ogni utilizzo (nessuna rottura, taglio, rigonfiamento, area irrigidita a molle, distacco, collasso) specialmente nell'area dei raccordi.
  - Ricorda di garantire la rintracciabilità di ogni singola pezzatura di tubo immessa nel mercato (CE 1935/2004, CE 2023/2006).



**Scan this code to receive further information** and regularly updated indications.

Otherwise consult the technical product sheets on

**[www.ivgspa.it](http://www.ivgspa.it)**



**Effettua la scansione del codice per avere ulteriori informazioni** e indicazioni regolarmente aggiornate.

Oppure consulta le schede tecniche prodotto su

**[www.ivgspa.it](http://www.ivgspa.it)**

## SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on [www.ivgspa.it](http://www.ivgspa.it).

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

**For safety reasons, never exceed the working pressure indicated in the product data sheet.**

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department ([marketing@ivgspa.it](mailto:marketing@ivgspa.it)).