



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	IVG Colbachini S.p.A.		
Address	Via Fossona 132, Cervarese S. Croce - PD -, 35030, Italy		
Type	Flexible Hoses		
Description	Flexible Exhaust Gas Rubber Hose Amalfi Cord, Amalfi LL & Amalfi LO		
Trade Name	IVG Amalfi		
Application	Water cooled diesel exhaust gas system installed on small craft less than 24m in length or pleasure yacht.		
Specified Standard	Lloyd's Register's Rules and Regulations for the Classification of Special Service Craft ISO 13363:2016 Rubber and Plastics Hoses for Marine-Engine Wet-Exhaust Systems – Specification SAE J2006: 2013		
Ratings	Sizes (Internal Diameter);	Amalfi Cord:	19 to 450mm
		Amalfi LL:	16 to 75mm
		Amalfi LO:	16 to 305mm
	Pressure;	Minimum burst pressure: 2.5 bar	
	Temperature;	-30°C to +100°C	

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Mattia Macri

Engineering Piping– Senior Specialist to
Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Other Conditions

1. Exhaust components are to be selected and installed in accordance with the manufacturer's instructions and recommendations and Lloyd's Register's Rules and Regulations for the Classification of Special Service Craft.
2. Service length should be as short as practicable, erosion/corrosion resistant shut off flaps or other devices are to be fitted on the hull side shell or pipe end and acceptable arrangements made to prevent water flooding the space.
3. Where it is intended to use flexible exhaust hoses in exhaust piping systems on craft or yachts Classed or intended to be classed by LR, the arrangements are to be submitted for approval.
4. The following details are to be permanently marked:
 - Manufacturer's name or trademark.
 - Designation type reference.
 - Nominal diameter.
 - Pressure rating.
 - Temperature range.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR2003044TA

The Design Appraisal Document LR2536277DA and its supplementary Type Approval Terms and Conditions form part of this Certificate.