

Montreal 20

Water discharge hose



Application:

softwall discharge hose for water, non corrosive fluids and compressed air; used in construction sites, industries and agriculture.

Used in construction sites and industries
Length up to 120 m
High strength synthetic cord, 20 bar W.P.

Tube:

black, smooth, synthetic rubber.

Reinforcement:

high strength synthetic cord.

Cover:


black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

Temperature:

from -35°C (-31°F) to +70°C (+158°F).

Branding:

continuous green stripe "IVG Water (family logo)...".



Montreal 20



Code	Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1265571	13	1/2	19,5	0,77	20	300	60	900	0,22	0,15	120	400
1017683	19	3/4	29	1,14	20	300	60	900	0,47	0,32	120	400
1207032	25	1	35	1,38	20	300	60	900	0,6	0,40	120	400
1144120	32	1-1/4	44	1,73	20	300	60	900	0,92	0,62	120	400
1115448	38	1-1/2	50	1,97	20	300	60	900	1,07	0,72	120	400
1018310	51	2	65	2,56	20	300	60	900	1,56	1,05	120	400
1170023	63,5	2-1/2	80	3,15	20	300	60	900	2,41	1,62	120	400
1415697	76	3	90	3,55	20	300	60	900	2,32	1,56	120	400
1269461	90	3-35/64	112	4,41	20	300	60	900	4,47	3,00	120	400
1117009	102	4	120	4,73	20	300	60	900	3,83	2,57	120	400
1411390	203	8	223	8,79	20	300	60	900	7,82	5,26	60	200

Variants available on request:

1. Different diameters.
2. Yellow or blue hose cover.
3. Different working pressures.

Recommended Couplings:



Rapid



Camlock



Storz

