

Durana LL

Water suction and discharge hose



Application:

hardwall hose for suction and discharge of water and non corrosive liquids, suitable to be rolled up on mono-spiral hose reels. The robust construction enables the hose to withstand its weight without flattening. They are typically used in construction sites and daylight mines to spray water in order to prevent the dust from raising and in carbon deposits.

No flattening, robust
Suitable to be rolled up on hose reel
Weathering and ozone resistant

Tube:

black, smooth, synthetic rubber.

Reinforcement:

high strength synthetic cord, and helix wire.

Cover:

black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

Temperature:

from -30°C (-22°F) to +70°C (+158°F).

Branding:

continuous green stripe "IVG Water (family logo)..."



Durana LL



Code	Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Min. Reel size		Vacuum	Length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch		bar	m
1410903	38	1-1/2	55	2,17	10	150	40	600	1,62	1,09	550	21,7	0,9	120	400
1342207	51	2	68	2,68	10	150	40	600	2,32	1,59	700	27,6	0,9	120	400
1259652	63,5	2-1/2	82,5	3,25	10	150	40	600	3,28	2,20	900	35,5	0,9	120	400
1409875	76	3	97	3,82	10	150	30	450	4,03	2,71	1050	41,4	0,9	120	400
1378961	100	3-15/16	127	5,00	10	150	30	450	6,61	4,44	1400	55,2	0,9	120	400

Variants available on request:

1. Different diameters
2. Different working pressures.

