

WS/EN 45545

Rail brake hose



Specifications:

Technical Specification Trenitalia n° 373407 esp. 03. EN 45545-2:2023 HL3 R22 and R23.
Specification Mercitalia n° 377715 esp. 00.

Application:

softwall hose designed as a flexible connection in air brake systems on rail carriages and locomotives. It is fire resistant with low toxicity and low smoke emission.

Coils: supplied usually in application lengths with tapered ends.

According to EN 45545-2
Supplied in working lengths
Fittings available



Tube:

black, smooth, synthetic rubber.

Reinforcement:

high strength synthetic cord.

Cover:

black, smooth (wrapped finish), long lasting rubber, weathering, ozone, and oil resistant.

Temperature:

from -25°C (-13°F) to +80°C (+176°F).

Branding:

embossed stripe "IVG/class.../quarter and year of production" and coloured transfer stripe.



WS/EN 45545



Code	Inside diameter		Outside diameter		Burst pressure		Weight nominal		Length max	
	mm	inch	mm	inch	bar	psi	kg/m	lbs/ft	m	ft
1497316	13	1/2	23,5	0,93	75	1125	0,41	0,28	60	200
1700266	16	5/8	26,5	1,04	75	1125	0,47	0,32	60	200
1700267	22	55/64	37	1,46	75	1125	0,94	0,63	60	200
1498142	28	1-7/64	45	1,77	75	1125	1,31	0,88	60	200
1497324	38	1-1/2	56	2,20	75	1125	1,77	1,19	60	200

Variants available on request:

1. Rail couplings.

SPECIAL DETAILS

WARNINGS AND PRECAUTIONS

Rubber hoses have a service life proportional to their usage.

The equipment and systems where the hose is installed must be designed to ensure safe operation. Given the wide range of possible applications, IVG Colbachini does not guarantee suitability for all specific uses. The selection of the most appropriate product for the intended application, ensuring the required performance and safety standards, is the sole responsibility of the user.

IVG Colbachini shall therefore not be held liable for any use other than those indicated in its catalogues, product data sheets, quotations, order confirmations, or any accompanying recommendations.

Improper product selection and/or use, or failure to comply with installation, operation, maintenance, and storage procedures, may result in hose failure and cause damage to property or personal injury.

IVG Colbachini manufactures and markets both assembled hoses and hoses supplied without fittings.

Assembled Hoses

Before being placed on the market, the hose assembly is subjected by IVG to manufacturing control tests carried out by qualified personnel.

IVG declines all responsibility for any subsequent modifications, disassembly, or reinstallation of fittings performed by the user, as well as for uses that differ from those indicated in the product data sheet or in the absence of maintenance programs and periodic inspections.

Hoses and Fittings as spare parts

The user is responsible for assembling the hose and fittings, ensuring proper hose/fitting compatibility and compliance with the technical specifications for use. It is recommended that the hose assembly be subjected to a pressure tightness test carried out by qualified personnel.

IVG declines all responsibility in this regard.

Precautions

For proper selection and correct use of IVG products, reference should also be made to the recommendations issued by Assogomma, available at www.ivgspa.it, in accordance with ISO 8331 regarding installation, maintenance, methods and duration of use, as well as fitting stability and tightness.

For safety reasons, the working pressure indicated in the product technical data sheet must never be exceeded.

In general, continuous operation at maximum allowable pressure and/or temperature may significantly reduce the hose service life. Regular inspections and hydrostatic testing at the specified test pressure must therefore be carried out. Hydrostatic tests must be performed by adequately trained personnel using suitable equipment and in accordance with recognized testing standards.

For specific applications of rubber hoses, reference should be made to applicable legal requirements or compliance standards. Additional recommendations are available for particularly critical applications. For further information, please contact info@ivgspa.it.