


Tasmania

Fuel and oil delivery hose



Application:

softwall hose used for the delivery of petroleum products with aromatic content up to 50%.

Wide temperature range

Aromatic content up to 50%

Length up to 120 m

Tube:

black, smooth, NBR dissipative rubber.

Reinforcement:

high strength synthetic cord and antistatic copper wire.

Cover:

black, smooth (wrapped finish), NBR rubber, weathering and oil resistant.

Temperature:

from -35°C (-31°F) to +80°C (+176°F).

Branding:

continuous yellow stripe "IVG Oil (family logo)..."



Tasmania



Code	Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1491601	19	3/4	29	1,14	10	150	30	450	0,47	0,32	120	400
1490540	25	1	35	1,38	10	150	30	450	0,58	0,39	120	400
1494040	32	1 1/4	42	1,65	10	150	30	450	0,72	0,48	120	400
1491598	38	1 1/2	48,5	1,91	10	150	30	450	0,91	0,61	120	400
1490559	51	2	61,5	2,42	10	150	30	450	1,18	0,79	120	400
1495054	63,5	2 1/2	75	2,95	10	150	30	450	1,63	1,10	120	400
1494058	76	3	91	3,58	10	150	30	450	2,41	1,62	120	400
1495062	90	3 35/64	105	4,13	10	150	30	450	2,82	1,89	120	400
1490567	102	4	117	4,61	10	150	30	450	3,18	2,14	120	400

Variants available on request:

1. Hardwall Tampa hose with smooth cover.
2. Different diameters.
3. Different working pressures.

Recommended Couplings:



TW EN 14420-6



Fuel Italian Type coupling



Camlock EN 14420-7 (DIN 2828)

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).